

ID6 Identification Lighthouse

6-LED Surface Mount



M40

Dual Memory Capability

Wide view



FEATURES

- Dual Memory capability for cross function or cross state applications.
- Extra steady on functions for vehicle identification or illumination.
- Memory override for instant emergency use.
- Wrap around side optic for wider visibility.
- Low profile for discreet mounting.
- Multiple units are synchronizable and can flash simultaneously or alternately.
- Reverse polarity protection.
- Weatherproof and vibration resistant design.
- Aluminum base for heat dissipation.

SPECIFICATIONS

Meets: SAE J595 Class 1, ECE R65 (XA1, XB1), ECE R10-04

Bulb: High-power LED x 6pcs

Warning Patterns: 15 Flash Patterns (w/ 8 Modes per FP)

Operating Voltage: 12-24VDC

Avg. Current: 0.5A @12VDC / 0.25A @24VDC
(varies with flash pattern)

Avg. Power: 6 Watts (varies with flash pattern)

Max. Current: 1A @12VDC / 0.5A @24VDC

Max. Power: 12 Watts


Wires: Red-Vcc : 25cm (20AWG)
Black-GND : 25cm (20AWG)
Yellow-Flash Patterns & Sync : 25cm (20AWG)

Fuse Recommended: 2A

Multi-Unit Synchronization: Over 15 units

Available in: RED , BLUE , AMBER , WHITE

DIMENSIONS



PART NO.

- M40-0113A-00 (AMBER)
- M40-0113K-00 (AMBER/WHITE)
- M40-0113R-00 (RED)
- M40-0113U-00 (RED/WHITE)
- M40-0123A-00 (R65_AMBER)
- M40-0113B-00 (BLUE)
- M40-0113Q-00 (RED/BLUE)
- M40-0113T-00 (BLUE/WHITE)
- M40-0113W-00 (WHITE)
- M40-0123B-00 (R65_BLUE)

FLASH PATTERN

FP#	Flash Patterns	
1	Double (R65)	9 Quint (SAE)
2	Single (2Hz)	10 Mega
3	Triple (2Hz)	11 Ultra (SAE)
4	Quad (2Hz)	12 Single-Quad
5	Random	13 Single H/L
6	Single (SAE)	14 Steady&Warning*
7	Double (SAE)	15 Full Steady**
8	Quad (SAE)	

Warning (FP#1-13) comes with 8 Modes.

*Steady&Warning (FP#14) comes with 8 Modes.

**Full Steady (FP#15) comes with 6 Modes.