

Technical Specification

Radio Remote Speaker Microphone (RSM)	
Connectivity	Specifications
Dimension	85*58*29 (mm)
Weight	130g
IP Rating	IP66
Compatible Radio Model	Motorola
	M5: GP328plus, GP338plus, GP344, GP388, PTX760Plus, EX500, EX600, GL2000
	M7: DP4000, DP4400, DP4600, DP4401, DP4601; DP3400/3401/3600/3601 XPR6300, XPR6500, XPR6550, XiRP8268, XiRP8608, XiRP8668, XiRP8200, XiRP8208, MTP850S;
	M11: XPR3300, XPR3500, XiRP6600, XiRP6620, DP2000/2400/2600, DP3441 MTP3000/3500/3550
	TeloPTT Device: TE580, TE590
	Hytera
	H5: PD70X, PD78X, PT580H, PT580H Plus H8: PD60X/66X/68X, X1e/X1p/Z1p
	Sepura SP2: STP8000/9000 Series
	Airbus: THR9, TH9, TH1N
	Kenwood K2: TK-280,TK-290,TK-380,TK-385,TK-390, TK-480,TK-481,TK-2140, TK-2180, TK-3140, TK-3148, TK-3180, TK-5210, TK-5400, TK-5310, NX-200/300
Camera	
Resolution	1920*1080P, 1280*720P
Field of View	140 Degrees
Night Vision	Support
Built-in Storage	32GB Standard, 64/128GB Option
Low Memory Alarm	Support
Recording	
Video Quality	Multiple Recording Resolutions 1920x1080p (30 FPS); 1280x720p (30 FPS)
Recording Format	H.264 .MP4
Date & Time Stamp	Yes
Low Battery Alarm	Yes
Record Led	Yes
Video Transfer	USB Interface

Photo	
Taking Photo	Support
Battery	
Туре	3000mAh Lithium Polymer Rechargeable Battery
Charging Time	4.5 Hours
Battery Life	9 Hrs Continuous@720p; 8 Hrs Continuous@1080p;
Low Battery Alarm	Support
Security	
Password Protect	6 Digit Security Code

Standard Accessories







Belt Clip



Power Plug

Option Accessories



Dock Epaulette



Camera Radio Cable



Chest Harness



Dock Clamp



Magnet Mount Kits



Centre Chest Harness

Reliable and Flexible

4/F, Chuangye Building, Seven-Star Park, Yu'an 2nd Road, Bao'an District, Shenzhen, China Tel: +86 755 86950766

Fax: +86 755 86950708

Email: sales@telosystems.com